

PN系列 (PN SERIES)

PN系列产品 PN processing reels

产品采用组合结构，主要材料采用进口ABS工程塑料注塑成型，具有表面平整、光滑、强度高、耐冲击、耐酸碱腐蚀，平衡性能好，平衡精度可达6.3级以上，重量轻等特点，较木盘、铁盘优势非常明显。

This series reels are assembled structure, it is injected by brand new ABS plastic material. With the characteristic of smooth surface, high intension, impacted, anti-acid, good balance (up to 6.3 grade), light weight, it is superior to the wood reel and steel reels colligating the above characteristic.

标准类别产品 Standard PN reels

PN系列广泛用于各种线缆、线材的束丝、挤出、对绞、缠绕、编织、成缆设备生产过程中的收、放线，可在生产过程中重复使用。

PN reels widely used in the payoff & takeup during bunching, extrusion, twisting, wrapping, braiding, cabling, and normally it recycling used in the cable factory.

序号	型号	结构	材料	瓣板径 d1	筒径 d2	孔径 d3	内宽 L2	全长 L1	瓣板厚 S	排孔					
										f	e1-e2				
1	PN300A	组合 ABS	ABS	300	130	36, 40	178, 220	205, 245	12	7.5	38-48				
2	PN300C											155, 185, 250	185, 215, 280	15	38-62
3	PN315											130	178, 185, 220	210, 215, 250	41.5-47
4	PN350											160	160, 200, 250	200, 240, 290	44-59
5	PN400A											200	250, 263, 265, 280, 315	300, 312, 350	60-75
6	PN400B											160	200, 250	240, 290	45-63
7	PN400D											200	250, 280, 315	290, 320, 355	53.5-73.5
8	PN450A											450	265, 280	300, 320, 355	49.5-70.5
9	PN450B											225	265, 280	305, 320	50-87
10	PN500A											250	250, 270, 280, 315	300, 310, 320, 375	70-100
11	PN500B											200	250, 280, 315	300, 320, 330, 375	70.5-97.5
12	PN500D	250	250, 315	300, 375	63-73										
13	PN500E	550	56	290, 320, 355	70-99										
14	PN550A	200	56, 80	300, 330, 365	80										
15	PN550B	250	250, 315, 400	310, 375, 460	70.5-97.5										
16	PN550A	560	56	335, 370	80										
17	PN560C	280	280, 315	322, 357	83										
18	PN560D	127	315, 325, 350, 400	375, 380, 400, 450	70-98										
19	PN600	250	315, 350, 400, 415	375, 400, 475	69-98										
20	PN630A	630	315, 400, 415, 500	375, 475, 550	70-97.5										
21	PN630B	315	315, 400, 415, 440	375, 475, 500	115-120										
22	PN700	250	400, 415, 450, 500	475, 490, 520, 600	115-160										
23	PN800A	800	400, 450, 500, 550	475, 600	115-167										
24	PN800B	400	630	750											
25	PN1000	1000	507	40											

